

HULME MARTIN HEAT SEALERS

Hulme Martin Heat Sealers Ltd Unit 5B, Country Business Centre White Cottage Farm Lucas Green Road, West End Woking, Surrey GU24 9LZ Tel: 01483 476767 Fax : 01483 486343 Email: info@hulmemartin.co.uk

www.hulmemartin.co.uk

HIBOOC Compared to the second second

(Foot Operated, Medium Capacity Impulse Heat Sealer) – Part No. 13002161

Maximum Sealing Length	340mm (13")
Seal Width	3mm (Standard)
Film Thickness	2 x 1000 gauge (2 x 250 micron)
Voltage	240V, 110V (Conversion)
Power Consumption (Watts)	325W (per seal)
Fuse Rating	T 3.15 amp
Footprint	454mm (L) x 190mm (W) x 190mm (H)
Weight	10.7 Kg
Operation	Foot Operated (via Chain & Pedal)
Mounting	Bench Mounted
Options	Stand Kit, Rollers/Brackets & Retainers
	(for Layflat Tubing)

The HM 1300 CD (Dual Timer with Cutter) - Medium Capacity Impulse Heat Sealer

A general-purpose foot operated machine, providing great flexibility of operation. Leave hands free to manipulate large or heavy packages.

Simple bench mounting or optional stand available.

This CD model has a Dual Electronic Timer for complete control of the heating & cooling cycle, with a cutter to facilitate bag production from lay flat tubing.

This machine is simple to maintain with consumable spares being easy to fit & available from stock.