

## HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd Unit 5B, Country Business Centre White Cottage Farm Lucas Green Road, West End Woking, Surrey

> GU24 9LZ Tel: 01483 476767 Fax : 01483 486343

Email: info@hulmemartin.co.uk



(Hand Operated, Standard Impulse Heat Sealer) - Part No. 30001061

(Hand Operated, Standard Impaise Heat Sealer) Trait No. 3000 1001	
<b>Maximum Sealing Length</b>	310mm (12.5")
Seal Width	3mm (Standard)
Film Thickness	2 x 1000 gauge (2 x 250 micron)
Voltage	240V, 110V (Conversion)
Power Consumption (Watts)	300W (per seal)
Fuse Rating	T 3.15 amp
Footprint	455mm (L) x 139mm (W) x 190mm (H)
Weight	8.5 Kg
Operation	Hand Operated
Mounting	Bench Mounted
Options	6mm (Wide Seal), T-wire (Seal-Cut-
	Seal), Round Wire (Cut-&-Seal), Rollers
	& Brackets (for Layflat Tubing)

The HM 3000 (E/Standard) – Standard Impulse Heat Sealer

General purpose machines with many applications.

Used extensively by hospitals, laboratories, retailers, engineering & other industries. This standard model has a Single Electronic Timer for control of the heating cycle only.

The machine is simple to maintain with consumable spares being easy to fit & available from stock.