

HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd Unit 5B, Country Business Centre White Cottage Farm Lucas Green Road, West End Woking, Surrey

> GU24 9LZ Tel: 01483 476767 Fax : 01483 486343

Email: info@hulmemartin.co.uk



(Foot Operated, Large Capacity Impulse Heat Sealer) - Part No. 65012051

(i sor specialca, zarge capacity impaise recar scarce, rainties sor i zor	
Maximum Sealing Length	660mm (26")
Seal Width	3mm (Standard)
Film Thickness	2 x 1000 gauge (2 x 250 micron)
Voltage	240V, 110V (Conversion)
Power Consumption (Watts)	360W (per seal)
Fuse Rating	T 3.15 amp
Footprint	851mm (L) x 180mm (W) x 190mm (H)
Weight	19.5 Kg
Operation	Foot Operated (via Cable & Pedal)
Mounting	Bench Mounted
Options	Stand Kit, Rollers/Brackets (for Layflat
	Tubing), 6mm (Wide Seal), Round Wire
	(Cut-&-Seal), T-Wire (Seal-Cut-Seal)

The HM 6500 DL (Foot Peal & Cable Operated) – Large Capacity Impulse Heat Sealer

Large capacity general purpose foot operated impulse sealing machines for industrial, warehousing & mail order applications.

Simple bench mounting or optional stand available.

This DL model has a Dual Electronic Timer for complete control of the heating and cooling cycles. It also has a cable operated foot pedal which allows increased flexibility of installation.

Another advantage is that the foot pedal is of a lever action design, which helps to minimise operator effort.

This machine is simple to maintain with consumable spares being easy to fit & available from stock.