

HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd Unit 5B, Country Business Centre White Cottage Farm Lucas Green Road, West End Woking, Surrey GU24 9LZ

Tel: 01483 476767 Fax : 01483 486343 Email: info@hulmemartin.co.uk



HM 3100 DS (Semi-Automatic Heat Sealer) - Part No. 31032051

Maximum Sealing Length	310mm (12.5")
Seal Width	3mm (Standard Seal)
Film Thickness	2 x 1000 gauge (2 x 250 micron)
Voltage	240V, 110V (Conversion)
Power Consumption (Watts)	300W (per seal)
Fuse Rating	T 3.15 amp
Footprint	400mm (L) x 340mm (W) x 150mm (H)
Weight	15.5 Kg
Operation	Foot or Hand Operated via Pad Switch
	(with Hold Down Latch & Security
	Keys)
Mounting	Bench Mounted
Options	6mm (Wide Seal), T-Wire (Seal-Cut-
	Seal), Round wire (Cut-&-Seal), Rollers
	& Brackets (For Lay Flat Tubing)

The HM 3100 DS - Semi-Automatic Heat Sealer

General purpose Semi-Automatic Solenoid operated machine, with many applications. Used extensively by hospitals, laboratories, retailers, engineering & other industries. Simple bench mounting. This DS model has a Dual Electronic Timer, for complete control of the heating & cooling cycle.

It is controlled via a one touch Pad Switch that can be operated by hand or foot.

This machine is simple to maintain with consumable spares being easy to fit & available from stock.