

## HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd Unit 5B, Country Business Centre White Cottage Farm Lucas Green Road, West End Woking, Surrey

> Tel: 01483 476767 Fax: 01483 486343

**GU24 9LZ** 

Email: info@hulmemartin.co.uk



D545-AH All In Sealer

The HM D 545-AH, a compact, horizontal & continuous band sealer, with a semi-automatic functionality.

With an Epoxy covering, this bench mounted heat sealer will ensure pre-made bags are sealed, lying flat.

All operating parameters are controlled by a Digital Control Panel (including an automatic cool down function).

By using PTFE (Teflon) seal belts, a number of different materials can be sealed: polyethylene, polypropylene, cellophane, paper, aluminium & other laminates.

The conveyor belts height & distance position is able to be adjusted to the users' needs. The maximum distance between the seal and the top of the bag is 30mm.

The integrated conveyor belt is adjustable in height, & can be pulled out up to 70mm towards the operator (for larger products).

The temperature (adjustable up to a maximum of 250°C), running speed & cooling (by means of a special fan) are all easily adjustable via an easy-to-use Digital Control Panel.

## **Options:**

- Textured Seal (Diamond Shape)
- 9 pre-set seal settings (for different packaging types)





## HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd Unit 5B, Country Business Centre White Cottage Farm Lucas Green Road, West End Woking, Surrey

> Tel: 01483 476767 Fax : 01483 486343

**GU24 9LZ** 

Email: info@hulmemartin.co.uk



The integrated conveyor has a flow rate of up to max 10 meters per minute (depending on the film thickness).

The conveyor is manually adjustable in distance (Increases max bag length by 100mm).

This enables you to seal bags with different sizes in length, widths & thicknesses.

**Applications:** All kinds of sealable bags, food products, seeds, ironware, mechanical and electrical parts etc.

## HM D545-AH - All In Sealer - Continuous Band Sealer

Maximum Sealing Length	Continuous Sealing System
Seal Width	10mm (Flat Seal)
Film Thickness (for weld)	2 x 25 Micron (Min), 2 x 200 Micron (Max)
Seal Temperature (Degrees Centigrade)	25°C (Min) - 250°C (Max)
Footprint	613mm (L) x 457mm (W) x 267mm (H)
Weight	30kg
Max. Weight on Conveyor Belt	5kg
Conveyor Belt Size	112mm (W) x 670mm (L) (with Input Plate)
Conveyor Operating Speed	Adjustable (0 up to 10m per min)
Voltage	230V, 13amps (Single Phase)
Power Consumption (Watts)	1100W (Max)
Operation  Mounting	Manually Operated, Conveyor (Use in a well ventilated area), Digital Control Panel, Type of product: Granulate, Powder & Solid, Product Infeed from Right to Left Bench Mounted
Options	Textured Seal (Diamond Shape), 9 x Pre-Set Seal Settings

Packaging Examples: Coffee, Confectionery & Seed







